Transmission specifications catalog

Powering Business Worldwide

This document contains product specifications for current and discontinued Eaton and Eaton Cummins manual and automated manual transmissions.

Auxiliary 2, 3, & 4 Speed

MODEL 2 SPEED AUXILIARY	Sales Sht. TRSL-XXX	Lbs-Ft. Max TQ.	Over All	REVERSE	1	%	2	Midship	Oil Cap Pints	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
AT-1202	-3900	17500	2.04	--	2.04	104	1.00	STD	11	16.5	353	93
2-A-92	-3900	9700	2.30	--	2.30	130	1.00	STD	12	16.2	310	--
2-B-92	-3901	9701	2.30	--	2.30	131	1	STD	12	16.2	310	--

MODEL 2 SPEED AUXILIARY	Sales Sht. TRSL-XXX	Lbs-Ft. Max TQ.	Over All	REVERSE	HIGH	%	LOW	Midship	Oil Cap Pints	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
2-A-62	--	--	--	--	1.00	--	1.58	STD	7	14.9	165	--
2-B-62	--	--	--	--	1.00	--	1.33	STD	7	14.9	165	--
2-B-62 (OPTIONAL)	--	--	--	--	2.00	--	1.33	STD	7	14.9	165	--

MODEL 3 SPEED AUXILIARY	Sales Sht. TRSL-XXX	Lbs-Ft. Max TQ.	Over All	REVERSE	HIGH	INTER-MEDIATE	LOW	Midship	Oil Cap Pints	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
3-A-65	--	--	--	--	0.75	1.00	2.23	STD	12	19.0	262	94
3-B-65	--	--	--	--	0.80	1.00	1.24	STD	12	19.0	262	94
3-C-65	--	--	--	--	0.75	1.00	1.24	STD	12	19.0	262	94
3-D-65	--	--	--	--	0.80	1.00	2.23	STD	12	19.0	262	94
3-E-65	--	--	--	--	0.80	1.00	1.74	STD	12	19.0	262	94
3-F-65	--	--	--	--	0.75	1.00	1.74	STD	12	19.0	262	94
3-G-65	--	--	--	--	1.00	1.32	2.23	STD	12	19.0	262	94
3-H-65	--	--	--	--	1.00	1.32	1.74	STD	12	19.0	262	94
3-J-65	--	--	--	--	0.86	1.00	1.17	STD	12	19.0	262	94
3-K65	--	--	--	--	0.78	1.00	2.18	STD	12	19.1	262	94
3-L-65	--	--	--	--	0.78	1.00	1.24	STD	12	19.1	262	94
3-M-65	--	--	--	--	0.86	1.00	1.75	STD	12	19.1	262	94
3-P-65	--	--	--	--	1.00	1.32	2.18	STD	12	19.1	262	94
3-Q-65	--	--	--	--	1.00	1.32	1.75	STD	12	19.1	262	94
3-A-92	--	--	--	--	0.75	1.00	2.09	STD	12	22.6	380	1.08
3-B-92	--	--	--	--	0.84	1.00	1.24	STD	12	22.6	380	1.08
3-C-92	--	--	--	--	0.75	1.00	2.64	STD	12	22.6	380	1.08
3-D-92	--	--	--	--	0.75	1.00	1.24	STD	12	22.6	380	1.08
3-E-92	--	--	--	--	0.84	1.00	2.09	STD	12	22.6	380	1.08
3-F-92	--	--	--	--	0.84	1.00	2.64	STD	12	22.6	380	1.08
3-G-92	--	--	--	--	1.00	1.33	2.09	STD	12	22.6	380	1.08
3-H-92	--	4000	--	--	1.00	1.33	2.64	STD	12	22.6	380	1.08
3-TA-92	--	--	--	--	0.75	1.00	2.09	STD	26	22.6	608	1.175 / 1.345
3-TC-92	--	--	--	--	0.75	1.00	2.64	STD	26	22.6	608	1.175 / 1.345
3-TD-92	--	--	--	--	0.75	1.00	1.24	STD	26	22.6	608	1.175 / 1.345

MODEL 4 SPEED AUXILIARY	Sales Sht. TRSL-XXX	Lbs-Ft. Max TQ.	Over All	OVER-DIRVE	DIRECT	SECOND	FIRST	Midship	Oil Cap Pints	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
4-B-75	--	--	--	0.85	1.00	1.24	2.22	STD	12	22.6	370	92
4-C-75	--	--	--	0.85	1.00	1.18	2.22	STD	12	22.6	370	92
4-D-75	--	--	--	0.84	1.00	1.24	2.29	STD	13	22.6	378	92
4-E-75	--	--	--	0.94	1.00	1.18	2.29	STD	13	22.6	378	92

MODEL 4 SPEED	Sales Sht. TRSL-XXX	Lbs-Ft. Max TQ.	FOURTH	THIRD	SECOND	FIRST	REVERSE	Midship	Oil Cap Pints	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
4-AI-86	--	--	1.00	1.76	3.27	6.54	7.24	STD	17	23.9	475	97
4-AI-86	--	--	1.00	1.76	3.27	5.55	6.58	STD	17	23.9	475	97
4-AI-86	--	--	0.76	1.00	1.86	3.72	4.12	STD	17	23.9	475	97
4-A-112	--	--	1.00	1.76	3.27	6.54	6.49	STD	18	25.8	525	R-.553 / L-.302
4-A-112 (OPTIONAL)	--	--	1.00	1.76	3.08	6.54	5.06	STD	18	25.8	525	R-.553 / L-.302
4MS1440	--	--	0.71	1.00	1.40	1.98	1.61	STD	24	35.3	720	R-92 / L-80
4MS1440 (OPTIONAL)	--	--	0.71	1.00	1.40	1.98	1.86	STD	24	35.3	720	R-92 / L-80
4MB1440	--	--	0.71	1.00	1.58	2.72	2.10	STD	24	35.3	720	R-92 / L-80

5, 6, & 7 Speed

MODEL 5 SPEED	Lbs-Ft. Max TQ.	Over All	Reverse	Reverse LL	Reverse L	Reverse H	1 Ratio	%	2	%	3	%	4	%	5	%	6	%	7	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
FS-4005A	420	8.05				8.05	8.05	85	4.35	78	2.45	66	1.48	48	1.00					20.4	232	46
FS-4005B	420	6.99				6.99	6.99	85	3.78	78	2.13	66	1.28	28	1.00					20.4	232	53
FS-4005C	420	6.99				6.99	6.99	85	3.78	78	2.13	81	1.17	17	1.00					20.4	232	53
FS-4205A	420	8.05				8.06	8.05	85	4.35	78	2.45	66	1.48	48	1.00					20.4	232	46
FS-4205B	420	6.99				6.99	6.99	85	3.78	78	2.13	66	1.28	28	1.00					20.4	232	53
FS-5005A	520	7.52				6.27	7.52	73	4.35	71	2.54	67	1.52	52	1.00					21.2	232	R-.46 / L-.44
FS-5005B	520	6.82				5.30	6.82	85	3.68	71	2.15	67	1.28	28	1.00					21.2	232	R-.54 / L-.52
FS-5005C	520	6.82				5.30	6.82	85	3.68	85	1.99	71	1.17	17	1.00					21.2	232	R-.54 / L-.52
FS-5205A	520	7.52				6.27	7.52	73	4.35	71	2.54	67	1.52	52	1.00					23.1	260	R-.46 / L-.44
FS-5205B	520	6.82				5.30	6.82	85	3.68	71	2.15	67	1.28	28	1.00					23.1	260	R-.54 / L-.51
FS-6105A	660	7.22				7.22	7.22	86	3.89	75	2.22	60	1.39	39	1.00					25.6	356	48
FS-6105B	660	7.22				7.22	7.22	86	3.89	75	2.22	75	1.27	27	1.00					25.6	356	48
FS-6205A	660	7.22				7.22	7.22	86	3.89	75	2.22	60	1.39	39	1.00					25.6	340	48
FS-6205B	660	7.22				7.22	7.22	86	3.89	75	2.22	75	1.27	27	1.00					25.6	340	48
FS-6305A	660	7.22				7.22	7.22	86	3.89	75	2.22	60	1.39	39	1.00					25.6	369	46
FS-6305B	660	7.22				7.22	7.22	86	3.89	75	2.22	75	1.27	27	1.00					25.6	369	46
T-905A	900	NA	6.48				6.35		3.75		2.38		1.54		1.00					27.6	429	53
T-905B	900	NA	6.48				6.35		3.75		2.04		1.16		1.00					27.6	429	53
T-905C	900	NA	7.12				7.23		3.92		2.16		1.18		1.00					27.6	429	51
T-905D	900	NA	5.55				5.45		3.23		2.04		1.32		1.00					27.6	429	--
T-905F	900	NA	7.12				7.23		3.92		2.16		1.45		1.00					27.6	429	51
T-905H	900	NA	6.48				6.92		3.75		2.37		1.54		1.00					24.7	429	53
T-905J	900	NA	7.12				7.23		4.09		2.56		1.61		1.00					24.7	429	51
T-905G	900	NA	4.94				4.83		2.99		1.87		1.31		1.00					24.7	429	NA
T-905M	900	NA	5.58				5.47		2.67		1.76		1.32		1.00					27.6	429	NA
T-905P	900	NA	6.48				6.35		3.75		2.04		1.39		1.00					24.7	429	53
T-11605A	1150	6.35	6.48				6.35	69	3.75	57	2.39	57	1.52	52	1.00					24.7	407	R-.533 / L-.533
T-11605B	1150	6.48	6.48				6.35	69	3.75	84	2.04	75	1.16	16	1.00					24.7	407	R-.533 / L-.533
T-11605C	1150	7.20	7.09				7.20	85	3.90	84	2.12	80	1.18	18	1.00					24.7	407	R-.513 / L-.513
T-11605D	1150	5.46	5.57				5.46	69	3.23	57	2.05	57	1.31	31	1.00					24.7	407	R-.619 / L-.619
T-11605F	1150	7.20	7.09				7.20	85	3.90	84	2.12	46	1.46	46	1.00					24.7	407	R-.513 / L-.513
T-11605M	1150	5.46	5.57				5.46	105	2.66	52	1.75	34	1.31	31	1.00					24.7	407	R-.619 / L-.619
TO-905A	900	NA	4.21				4.12		2.44		1.54		1.00		0.65					27.6	429	82
TO-905B	900	NA	5.58				5.47		3.23		1.76		1.00		0.86					27.6	429	62
TO-905C	900	NA	6.01				6.11		3.31		1.82		1.00		0.84					27.6	429	61
TO-905D	900	NA	4.21				4.12		2.44		1.54		1.00		0.76					27.6		--
TO-905F	900	NA	4.90				4.97		2.69		1.48		1.00		0.69					24.7	429	74
TO-11605A	1150	6.35	4.25				4.16	69	2.46	57	1.57	57	1.00	52	0.66					24.7	407	R-.813 / L-.813
TO-11605B	1150	6.35	5.57				5.46	69	3.23	84	1.75	75	1.00	16	0.86					24.7	407	R-.619 / L-.619
TO-11605C	1150	7.20	6.03				6.12	85	3.32	84	1.80	80	1.00	18	0.85					24.7	407	R-.603 / L-.603
TO-11605D	1150	5.46	4.25				4.16	69	2.46	57	1.57	57	1.00	31	0.76					24.7	407	R-.813 / L-.813

5, 6, & 7 Speed

MODEL 6 SPEED	Lbs-Ft. Max TQ.	Over All	INT. REV.	Reverse LL	Reverse L	Reverse H	1 Ratio	%	2	%	3	%	4	%	5	%	6	%	7	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
FS-4106A	640 - 825					8.07	9.03	72	5.25	69	3.10	55	2.00	45	1.38	38	1.00			20.5	254	B-.23 / L-.43
FS-4106B	640 - 825					6.74	7.45	72	4.38	57	2.80	50	1.86	43	1.29	26	1.00			20.5	254	B-.27 / L-.52
FS-5206A	640 - 825					8.07	9.03	72	5.25	69	3.10	55	2.00	45	1.38	38	1.00			20.5	254	B-.23 / L-.43
FS-5206B	640 - 825					6.74	7.45	72	4.38	57	2.80	50	1.86	43	1.29	26	1.00			20.5	254	B-.27 / L-.52
FS-5106A	520	9.01				8.63	9.01	71	5.27	62	3.25	59	2.04	50	1.36	36	1.00			25.6	342	52
FS-5306A	520	9.01				8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1.00			25.6	342	52
FS-5406A	560	9.01				8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1.00			25.6	359	52
FS-5406N	560	9.01				8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1.00			25.6	359	52
FS-6106	660					8.00	9.00	80	5.01	69	2.96	56	1.89	43	1.32	32	1.00			28.5	416	46
FS-6106A	660	9.00				8.00	9.00	80	5.01	69	2.96	56	1.89	43	1.32	32	1.00			28.5	402	46
FS-6206	605					8.63	9.01	71	2.57	62	3.22	58	2.04	50	1.36	36	1.00			25.6	358	52
FS-6306A	660	9.01				8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1.00			25.6	345	52
FS-6406A	660	9.01				8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1.00			25.6	359	52
FS-6406N	660	8.84				8.46	8.84	64	5.39	61	3.34	54	2.17	50	1.45	45	1.00			25.6	345	52
FS-7206A	750	9.00				8.00	9.00	81	4.98	67	2.98	57	1.89	43	1.32	32	1.00			28.5	410	46
FS-8206A	820	9.00				8.00	9.00	81	4.98	67	2.98	57	1.89	43	1.32	32	1.00			28.5	398	46
FSB-5406B	560	8.03				7.70	8.03	59	5.06	64	3.09	58	1.95	49	1.31	1	1.00			25.6	359	52
FSB-6406B	660	8.03				7.70	8.03	59	5.06	64	3.09	58	1.95	49	1.31	1	1.00			25.6	359	52
FSO-4106B	640 - 825					5.43	9.03	72	6.08	69	3.56	55	2.12	37	1.37	26	1.00			20.5	254	B-.33 / L-.64
FSO-5206B	640 - 825					5.43	9.03	72	6.08	69	3.56	55	2.12	37	1.37	26	1.00			20.5	254	B-.33 / L-.64
FSO-6406A	660	9.04				6.75	7.05	71	4.13	64	2.52	58	1.59	59	1.00	28	0.78			25.6	359	68
FSO-8406A	860	9.04				6.75	7.05	71	4.13	64	2.52	58	1.59	59	1.00	28	0.78			25.6	359	68
RT-906	900	NA			2.73	10.24	9.27	58	5.85	56	3.76	54	2.47	58	1.56	56	1.00			30.9	565	70
T-955AL	950	NA			11.40	6.48	11.17		6.35		3.75		2.38		1.54		1.00			30.9	580	53
T-955ALL	950	NA	11.40	27.09	26.54	6.48	11.17		6.35		3.75		2.38		1.54		1.00			30.9	646.0	53
T-955GL	950	NA			7.41	4.21	8.51		4.84		2.99		1.87		1.31		1.00			30.9	580	70
T-1056A	1050	NA				8.18	8.90		5.22		3.07		1.82		1.34		1.00			30.9	515	--
T-1056AA	1050	NA				8.19	8.90	70	5.22	70	3.08	68	1.83	36	1.34	34	1.00			28.9	562	51
T-11606	1150	NA				8.15	8.86	70	5.20	69	3.08	68	1.83	37	1.34	34	1.00			28.9	556	51
TO-955AL	950	NA			7.41	4.21	7.26		4.13		2.44		1.54		1.00		0.65			30.9	580	82
TO-955ALL	950	NA	7.24	17.61	17.25	4.21	7.26		4.13		2.44		1.54		1.00		0.65			32.1	646.0	82
TO-955DL	950	NA			7.41	4.21	7.26		4.13		2.44		1.54		1.00		0.75			30.9	580	82
TO-955DLL	950	NA	7.41	17.25	7.41	4.23	7.26		4.13		2.44		1.54		1.00		0.75			32.1	646	82
TO-955S	950	NA			8.69	4.94	8.51		4.84		2.74		1.58		1.00		0.88			28.7	580	NA

5, 6, & 7 Speed

MODEL 7 SPEED	Lbs-Ft. Max TQ.	Over All	LO-LO	Reverse LL	Reverse L	Reverse H	1 Ratio	%	2	%	3	%	4	%	5	%	6	%	7	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
T-955ALL	950	NA	26.54	27.09	11.04	6.48	11.17		6.35		3.75		2.38		1.54		1.00			34.1	646	--
T-8607A	975	10.50			10.20		10.50	71	6.13	65	3.71	47	2.51	37	1.83	37	1.34	34	1.00	28.4	575	51
T-8607B	975	12.35			12.03		12.35	73	7.15	66	4.31	58	2.72	49	1.83	37	1.34	34	1.00	28.4	575	51
T-11607A	1150	10.20			10.20		10.50	71	6.13	65	3.71	48	2.51	37	1.83	37	1.34	34	1.00	28.9	576	R-.513 / L-.513
T-11607B	1150	12.03			12.03		12.35	73	7.15	66	4.31	58	2.72	49	1.83	37	1.34	34	1.00	28.9	576	R-.513 / L-.513
T-14607A	1400	10.50			10.20		10.50	71	6.13	65	3.71	48	2.51	37	1.83	37	1.34	34	1.00	28.9	575	51
T-14607B	1400	12.35			12.03		12.35	73	7.15	66	4.31	58	2.72	49	1.83	37	1.34	34	1.00	28.9	575	51
TO-955ALL	950	NA	17.25	17.61	7.41	4.21	7.26		4.13		2.44		1.54		1.00		0.65			34.1	646	--
TO-955DLL	950	NA	17.25	17.61	7.41	4.21	7.26		4.13		2.44		1.54		1.00		0.75			34.1	646	--
TX-8607B	975	12.35			8.99		9.24	73	5.35	66	3.22	58	2.04	49	1.37	37	1.00	34	0.75	28.4	575	69
TX-14607B	1400	12.35			8.99		9.24	73	5.35	66	3.22	58	2.04	49	1.37	37	1.00	34	0.75	28.9	575	69

8 Speed

MODEL 8 SPEED	Lbs-Ft. Max TQ.	Over All	LL	Reverse L	Reverse H	LL1	%	L	%	LL2	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
RT-11608	1150	10.23		12.74	3.33							10.23	42	7.23	38	5.24	37	3.83	43	2.67	42	1.89	38	1.37	37	1.00	28.9	577	R-.575 / L-.575
RT-14608	1450	10.23		12.74	3.33							10.23	42	7.23	38	5.24	37	3.83	43	2.67	42	1.89	38	1.37	37	1.00	29.5	604	R-.575 / L-.576
RTF-14608	1450	10.23		12.74	3.33							10.23	42	7.23	38	5.24	37	3.83	43	2.67	42	1.89	38	1.37	37	1.00	29.5	604	R-.575 / L-.576
RTO-11607L	1150	19.50		11.89	3.33			14.87	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76			29.5	605	R-.813 / L-.813
RTOF-11607L	1150	19.50		11.89	3.33			14.87	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76			29.5	605	R-.813 / L-.813

9 Speed

MODEL 9 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL1	%	L	%	LL2	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
L-1550	1450	NA		9.56	2.71							9.24		6.91		4.94		3.53		2.62		1.96		1.42		1.00		0.69	49.0	1350	RH. 74 / LH. 60
R-1150	890	NA		9.56	2.71							9.24		6.91		4.94		3.53		2.62		1.96		1.42		1.00		0.69	49.0	1350	RH. 74 / LH. 60
R-1160	890	NA		11.92	8.90							9.32		7.04		5.01		3.55		2.62		1.98		1.41		1.00		0.64	44.2	1160	RH. 66 / LH. 50
R-1160 (OPTIONAL)	890	NA		11.92	8.90							9.32		7.04		5.01		3.55		2.62		1.98		1.41		1.00		0.76	44.2	1160	RH. 66 / LH. 50
R-1550T	1450	NA		9.56	2.71							9.24		6.91		4.94		3.53		2.62		1.96		1.42		1.00		0.69	49.0	1350	RH. 74 / LH. 60
RT-6609A	660	12.72		12.08	3.53			12.72	48			8.61	37	6.27	35	4.66	36	3.42	36	2.52	37	1.83	35	1.36	36	1.00			28.4	376	72
RT-8608L	860	17.21		17.99	4.70			17.21	68			10.23	42	7.23	38	5.24	37	3.83	43	2.67	42	1.89	38	1.37	37	1.00			28.9	581	58
RT-8609	860	12.66		12.03	3.52			12.66	49			8.48	36	6.24	35	4.64	36	3.42	38	2.48	36	1.83	35	1.36	36	1.00			28.4	392	72
RT-8609A	860	12.66		12.03	3.52			12.66	49			8.48	36	6.24	35	4.64	36	3.42	38	2.48	36	1.83	35	1.36	36	1.00			28.4	392	72
RT-8709B	860	13.29		13.89	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			28.9	581	70
RT-909A	950			12.37	3.87			11.83	50			7.90	36	5.79	34	4.32	35	3.20	30	2.47	36	1.81	34	1.35	35	1.00			28.7	585	70
RT-9509A	950			12.37	3.87							11.83		7.90		5.79		4.32		3.20		2.47		1.81		1.35		1.00	30.9	585	70
RT-11509	1150			12.99	3.87			12.42				8.30		6.08		4.54		3.36		2.47		1.81		1.35		1.00			28.9	612	70
RT-11609A	1150	12.65		13.23	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			28.9	590	70
RT-11709H	1150	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			28.9	581	70
RT-12509	1250			13.07	3.87							12.50		8.35		6.12		4.56		3.38		2.47		1.81		1.35		1.00	32.4	680	70
RT-12609A	1250	12.65		13.23	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			28.9	583	70
RT-12709H	1250	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			28.9	583	70
RT-13609A	1350	12.65		13.23	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			28.9	588	70
RT-13709H	1350	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			28.9	588	70
RT-14609A	1450	12.65		13.23	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			29.5	607	70
RT-14709H	1450	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			29.5	607	70
RTF-909A	950			12.37	3.87			11.83	50			7.90	36	5.79	34	4.32	35	3.20	30	2.47	36	1.81	34	1.35	35	1.00			28.7	585	70
RTF-9509A	950			12.37	3.87							11.83		7.90		5.79		4.32		3.20		2.47		1.81		1.35		1.00	30.9	585	70
RTF-11609A	1150	12.65		13.23	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			28.9	590	70
RTF-11709H	1150	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			28.9	581	70
RTF-12509	1250			13.07	3.87							12.50		8.35		6.12		4.56		3.38		2.47		1.81		1.35		1.00	32.4	680	70
RTF-12609A	1250	12.65		13.22	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			28.9	602	70
RTF-13709H	1350	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			28.9	588	70
RTF-14609A	1450	12.65		13.23	3.89			12.65	51			8.38	35	6.22	36	4.57	34	3.40	38	2.46	35	1.83	36	1.34	34	1.00			29.5	616	70
RTF-14709H	1450	13.29		13.29	3.89			13.29	45			9.16	40	6.53	36	4.80	34	3.57	39	2.57	40	1.83	36	1.34	34	1.00			29.5	607	70
RTO-909A	950			9.17	2.86			8.77	50			5.85	36	4.29	34	3.20	35	2.37	30	1.83	36	1.34	34	1.00	35	0.74			28.7	585	94
RTO-909B	950			12.87	3.43			12.31	66			7.40	43	5.19	38	3.76	37	2.75	40	1.97	43	1.38	38	1.00	37	0.73			28.7	585	79
RTO-9509A	950			9.17	2.86							8.77		5.85		4.29		3.20		2.37		1.83		1.34		1.00		0.74	28.9	585	94
RTO-9509B	950			12.87	3.43							12.31		7.40		5.19		3.76		2.75		1.97		1.38		1.00		0.73	28.9	585	94
RTO-11509	1150			9.63	2.87			9.21				6.15		4.50		3.36		2.49		1.83		1.34		1.00		0.74			28.9	612	94
RTO-12509	1250			9.69	2.86							9.27		6.18		4.54		3.38		2.51		1.83		1.34		1.00		0.74	32.4	680	94
RTO-11609A	1150	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	590	94
RTO-11609B	1150	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	590	70
RTO-12609A	1250	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	602	94
RTO-12609B	1250	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	602	79
RTO-14609A	1450	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			29.5	616	94
RTO-14609B	1450	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			29.5	616	79

9 Speed

MODEL 9 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL1	%	L	%	LL2	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
RTO-11607LL	1150		18.53	11.89	3.33	23.18		14.87				8.79		5.59		3.57		2.46		1.57		1.00		0.76					33.6	676	R-.813 / L-.813
RTO-11707LL	1150	30.13	18.38	11.89	3.33	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	675	81
RTO-14608LL	1450		15.33	9.83	2.89	14.66	56	9.41	51			6.23	35	4.62	36	3.40	34	2.53	38	1.83	34	1.36	36	1.00	35	0.74			33.6	774	94
RTO-14708LL	1650	19.58	15.22	9.95	2.89	14.56	55	9.42	51			6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	35	0.74			33.6	766	94
RTO-11707DLL	1150	30.13	22.23	14.38	4.03	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	675	81
RTO-11709MLL	1150	35.71	25.21	15.76	4.15	26.07	60	16.29	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	41	1.38	38	1.00	37	0.73			33.6	694	81
RTO-11909MLL	1150		25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			33.1	694	79
RTO-13707DLL	1350	30.13	22.23	14.38	4.03	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	680	81
RTO-13707MLL	1350	33.16	25.29	14.38	4.03	25.29	70	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	32	0.76					33.6	756	81
RTO-14709MLL	1450	35.71	25.21	15.76	4.15	26.07	60	16.29	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			33.6	696	81
RTO-14909MLL	1450		25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			33.1	696	79
RTOF-909A	950			9.17	2.86			8.77	50			5.85	36	4.29	34	3.20	35	2.37	30	1.83	36	1.34	34	1.00	35	0.74			28.7	585	94
RTOF-909B	950			12.87	3.43			12.31	66			7.40	43	5.19	38	3.76	37	2.75	40	1.97	43	1.38	38	1.00	37	0.73			28.7	585	79
RTOF-9509A	950			9.17	2.86							8.77		5.85		4.29		3.20		2.37		1.83		1.34		1.00		0.74	28.9	585	94
RTOF-9509B	950			12.87	3.43							12.31		7.40		5.19		3.76		2.75		1.97		1.38		1.00		0.73	28.9	585	94
RTOF-11509	1150			9.63	2.87			9.21				6.15		4.50		3.36		2.49		1.83		1.34		1.00		0.74			28.9	612	94
RTOF-12509	1250			9.69	2.86							9.27		6.18		4.54		3.38		2.51		1.83		1.34		1.00		0.74	32.4	680	94
RTOF-11609A	1150	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	590	94
RTOF-11609B	1150	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	590	70
RTOF-12609A	1250	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	602	94
RTOF-12609B	1250	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	602	79
RTOF-14609A	1450	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			29.5	616	94
RTOF-14609B	1450	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			29.5	616	79
RTOF-11607LL	1150		18.53	11.89	3.33	23.18		14.87				8.79		5.59		3.57		2.46		1.57		1.00		0.76					33.6	676	R-.813 / L-.813
RTOF-11707LL	1150	30.13	18.38	11.89	3.33	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	675	81
RTOF-11707DLL	1150	30.13	22.23	14.38	4.03	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	675	81
RTOF-11709MLL	1150	35.71	25.21	15.76	4.15	26.07	60	16.29	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	41	1.38	38	1.00	37	0.73			33.6	694	81
RTOF-13707DLL	1350	30.13	22.23	14.38	4.03	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	680	81
RTOF-13707MLL	1350	33.16	25.29	14.38	4.03	25.29	70	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	32	0.76					33.6	756	81
RTOF-14708LL	1450	35.71	25.21	15.76	4.15	26.07	60	16.29	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			33.6	696	81
RTOF-14709MLL	1450		25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			33.1	696	79
RTLC-16609E	1650	14.71		14.71	3.89			14.71	44			10.20	39	7.34	40	5.26	39	3.78	40	2.70	39	1.94	40	1.39	39	1.00			32.4	695	70
RTLO-11707LL	1150	30.13	18.38	11.89	3.33	22.99	55	14.88	69			8.79	57	5.59	57	3.57	45	2.46	57	1.57	57	1.00	31	0.76					33.6	696	81
RTOC-16709A	1650	14.38		11.28	2.99			10.50	42			7.37	42	5.21	38	3.78	37	2.76	41	1.95	42	1.38	38	1.00	37	0.73			33.1	716	79
RTOC-16909A	1650	14.38		11.28	2.99			10.50	42			7.37	42	5.21	38	3.78	37	2.76	41	1.95	42	1.38	38	1.00	37	0.73			33.1	716	79
RTLOC-16909A-T2	1650	14.38		11.28	2.99			10.50	42			7.37	42	5.21	38	3.78	37	2.76	41	1.95	42	1.38	38	1.00	17	0.86	17	0.73	33.1	716	79
RTOC-18909A	1850	14.38		11.28	2.99			10.50	42			7.33	41	5.21	38	3.78	37	2.76	41	1.95	42	1.38	38	1.00	37	0.73			33.1	716	79
RTLOC-18909A-T2	1850	14.38		11.28	2.99			10.50	42			7.37	42	5.21	38	3.78	37	2.76	41	1.95	42	1.38	38	1.00	17	0.86	17	0.73	33.1	716	79
RTX-11509	1150			9.63	2.87			9.21				6.15		4.50		3.36		2.49		1.83		1.34		1.00		0.74			28.9	612	94
RTX-11609A	1150	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	590	94
RTX-11609B	1150	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	590	79
RTX-11609P	1150	12.70		11.06	2.89							10.58	40	7.55	40	5.39	41	3.83	38	2.77	40	1.97	40	1.41	41	1.00	20	0.83	28.9	589	94
RTX-11609R	1150	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	28.9	581	94
RTX-11709H	1150	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			28.9	581	79

9 Speed

MODEL 9 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL1	%	L	%	LL2	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
RTX-12509	1250			13.07	3.87							12.50		8.35		6.12		4.56		3.38		2.47		1.81		1.35		1.00	32.4	680	70
RTX-12609A	1250	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	602	94
RTX-12609B	1250	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	583	79
RTX-12609P	1250	12.70		11.06	2.89							10.58	40	7.55	40	5.39	41	3.83	38	2.77	40	1.97	40	1.41	41	1.00	20	0.83	28.9	601	94
RTX-12609R	1250	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	28.9	583	94
RTX-12709H	1250	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			28.9	583	79
RTX-13609A	1350	12.65		9.83	2.89			9.41	5			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	588	94
RTX-13609B	13.5	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	588	79
RTX-13609P	1350	12.70		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.83	28.9	588	94
RTX-13609R	1350	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	28.9	588	94
RTX-13709H	1350	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			28.9	588	79
RTX-14609A	1450	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			29.5	616	94
RTX-14609B	1450	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			29.5	607	79
RTX-14609P	1450	12.70		11.06	2.89							10.58	40	7.55	40	5.39	41	3.83	38	2.77	40	1.97	40	1.41	41	1.00	20	0.83	29.5	616	94
RTX-14609R	1450	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	29.5	607	94
RTX-14709B	1450	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			29.5	607	70
RTX-14709H	1450	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			29.5	607	79
RTX-16709B	1650	17.07		13.03	3.43			12.46	68			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			29.5	617	79
RTX-16709H	1650	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			29.5	617	79
RTX-14708LL	1650	19.58	15.22	9.95	2.89	14.56	55	9.42	51			6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	35	0.74			33.6	766	94
RTXF-11509	1150			9.63	2.87			9.21				6.15		4.50		3.36		2.49		1.83		1.34		1.00		0.74			28.9	612	94
RTXF-11609A	1150	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	590	94
RTXF-11609B	1150	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	590	79
RTXF-11609P	1150	12.70		11.06	2.89							10.58	40	7.55	40	5.39	41	3.83	38	2.77	40	1.97	40	1.41	41	1.00	20	0.83	28.9	589	94
RTXF-11609R	1150	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	28.9	581	94
RTXF-11709H	1150	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			28.9	581	79
RTXF-12509	1250			13.07	3.87							12.50		8.35		6.12		4.56		3.38		2.47		1.81		1.35		1.00	32.4	680	70
RTXF-12609A	1250	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	602	94
RTXF-12609B	1250	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	583	79
RTXF-12609P	1250	12.70		11.06	2.89							10.58	40	7.55	40	5.39	41	3.83	38	2.77	40	1.97	40	1.41	41	1.00	20	0.83	28.9	601	94
RTXF-12609R	1250	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	28.9	583	94
RTXF-12709H	1250	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			28.9	583	79
RTXF-13609A	1350	12.65		9.83	2.89			9.41	5			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			28.9	588	94
RTXF-13609B	13.5	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			28.9	588	79
RTXF-13609P	1350	12.70		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.83	28.9	588	94
RTXF-13609R	1350	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	28.9	588	94
RTXF-13709H	1350	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			28.9	588	79
RTXF-14609A	1450	12.65		9.83	2.89			9.41	51			6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74			29.5	616	94
RTXF-14609B	1450	17.21		13.14	3.43			12.57	68			7.47	42	5.28	38	3.83	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73			29.5	607	79
RTXF-14609P	1450	12.70		11.06	2.89							10.58	40	7.55	40	5.39	41	3.83	38	2.77	40	1.97	40	1.41	41	1.00	20	0.83	29.5	616	94
RTXF-14609R	1450	13.41		11.06	2.89							10.70	39	7.68	43	5.39	41	3.83	37	2.80	39	2.01	43	1.41	41	1.00	25	0.80	29.5	607	94
RTXF-14709H	1450	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			29.5	607	79
RTXF-16709B	1650	17.07		13.03	3.43			12.46	68			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			29.5	617	79
RTXF-16709H	1650	14.45		11.33	2.99			10.55	42			7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73			29.5	617	79
RTXF-14708LL	1650	19.58	15.22	9.95	2.89	14.56	55	9.42	51			6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	35	0.74			33.6	766	94

10 Speed

MODEL 10 SPEED LIGHTNING	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
FRLO-14410C	1450	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLO-15410C	1550	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLO-16410C	1650	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLO-14410C-T2	1450	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLO-15410C-T2	1550	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLO-16410C-T2	1650	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLOF-14410C	1450	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLOF-15410C	1550	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLOF-16410C	1650	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLOF-14410C-T2	1450	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLOF-15410C-T2	1550	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63
FRLOF-16410C-T2	1650	17.11		12.43	9.17					12.66	36	9.33	39	6.72	35	4.96	41	3.57	35	2.64	40	1.88	35	1.39	39	1.00	36	0.74	28.1	530	63

MODEL 10 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
FR-9210B	950	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FR-11210B	1150	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FR-12210B	1250	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FR-13210B	1350	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FR-14210B	1450	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FR-15210B	1550	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRF-9210B	950	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRF-11210B	1150	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRF-12210B	1250	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRF-13210B	1350	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRF-14210B	1450	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRF-15210B	1550	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRM-15210B	1550	14.80		16.21	3.63					14.80	34	10.95	36	8.09	34	5.97	38	4.46	35	3.32	36	2.45	34	1.81	35	1.35	34	1.00	29.9	592	65
FRO-11210B	1150	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FRO-11210C	1150	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-12210B	1250	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FRO-12210C	1250	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-13210B	1350	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FRO-13210C	1350	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-14210B	1450	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FRO-14210C	1450	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-15210B	1550	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FRO-15210C	1550	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-16210B	1650	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FRO-16210C	1650	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-17210C	1750	17.51		13.75	2.80					12.94	39	9.29	38	6.75	38	4.90	35	3.62	37	2.64	39	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FRO-18210C	1850	17.51		13.75	2.80					12.94	39	9.29	38	6.75	38	4.90	35	3.62	37	2.64	39	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FROF-11210B	1150	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FROF-11210C	1150	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FROF-12210B	1250	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FROF-12210C	1250	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84

10 Speed

MODEL 10 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
FROF-13210B	1350	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FROF-13210C	1350	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FROF-14210B	1450	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FROF-14210C	1450	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FROF-15210B	1550	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FROF-15210C	1550	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
FROF-16210B	1650	14.80		12.12	2.72					11.06	35	8.19	35	6.05	35	4.46	34	3.34	35	2.48	35	1.83	35	1.36	35	1.00	34	0.75	29.9	592	87
FROF-16210C	1650	17.17		13.75	2.80					12.69	37	9.29	38	6.75	38	4.90	35	3.62	40	2.59	37	1.90	38	1.38	38	1.00	35	0.74	29.9	592	84
R-96T	690			11.26	3.18					9.65		7.43		5.80		4.48		3.54		2.73		2.10		1.64		1.27		1.00	38.1	740 Iron 585 Alum	62
R-906T	690			11.26	3.18					7.43		5.80		4.48		3.54		2.76		2.10		1.64		1.27		1.00		0.78	38.1	740 Iron 585 Alum	63
RA-96T	690			11.26	3.18					9.65		7.43		5.80		4.48		3.54		2.73		2.10		1.64		1.27		1.00	38.1	740 Iron 585 Alum	62
RA-960T	690			11.26	3.18					7.43		5.80		4.48		3.54		2.76		2.10		1.64		1.27		1.00		0.78	38.1	740 Iron 585 Alum	63
RT-510	900	NA		9.50	2.77					9.00	28	1.02	28	5.48	29	4.26	24	3.43	31	2.62	28	2.05	28	1.60	29	1.24	24	1	27.9	425	NA
RT-610	600	NA		9.50	2.77					9.00	28	7.02	28	5.48	29	4.26	24	3.43	31	2.62	28	2.05	28	1.60	29	1.24	24	1	31.2	425	72
RTO-610	600	NA		7.66	2.23					7.25		5.66		4.42		3.43		2.76		2.11		1.65		1.29		1.00		0.80	31.2	425	72
RT-910	950			8.83	2.73					8.14	28	6.38	26	5.05	26	4.00	24	3.24	29	2.51	28	1.97	26	1.56	26	1.24	24	1.00	28.9	576	70
RT-1110	1100			9.71	2.74					9.71		7.49		5.83		4.55		3.55		2.74		2.11		1.65		1.27		1.00	30.9	620	70
RT-6610	660	8.94		9.50	2.78					8.94	28	7.00	28	5.46	28	4.26	25	3.42	31	2.61	28	2.05	28	1.60	28	1.25	25	1.00	28.3	359	72
RT-9710B	950	14.73		15.10	3.38					14.73	34	11.00	35	8.17	36	6.00	34	4.46	35	3.30	34	2.46	35	1.83	36	1.34	34	1.00	28.9	604	70
RT-11610	1150	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	28.9	598	70
RT-11710B	1150	14.73		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	604	70
RT-12510	1250			9.71	2.74					9.71		7.49		5.83		4.50		3.55		2.74		1.65		1.27		1.00			32.8	698	70
RT-12610	1250	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	28.9	609	70
RT-12710B	1250	14.78		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	606	70
RT-13710B	1350	14.78		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	611	70
RT-14610	1450	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	29.5	621	70
RT-14710B	1450	14.73		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	29.5	624	70
RT-7608LL	800	18.81	17.87	11.69	3.52	18.81	53	12.31	49	8.24	36	6.07	35	4.51	36	3.32	34	2.48	36	1.83	35	1.36	36	1.00					32.8	597	72
RT-8908LL	860	19.58	20.47	13.24	3.89	19.58	55	12.67	51	8.39	35	6.23	36	4.58	34	3.40	38	2.46	35	1.82	36	1.34	34	1.00					33.1	690	70
RTF-910	950			8.83	2.73					8.14	28	6.38	26	5.05	26	4.00	24	3.24	29	2.51	28	1.97	26	1.56	26	1.24	24	1.00	28.9	576	70
RTF-9710B	950	14.73		15.10	3.38					14.73	34	11.00	35	8.17	36	6.00	34	4.46	35	3.30	34	2.46	35	1.83	36	1.34	34	1.00	28.9	604	70
RTF-11610	1150	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	28.9	598	70
RTF-11710B	1150	14.73		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	604	70
RTF-12510	1250			9.71	2.74					9.71		7.49		5.83		4.50		3.55		2.74		1.65		1.27		1.00			32.8	698	70
RTF-12610	1250	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	28.9	609	70
RTF-12710B	1250	14.78		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	606	70
RTF-13710B	1350	14.78		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	611	70
RTF-14610	1450	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	29.5	621	70
RTF-14710B	1450	14.73		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	29.5	624	70
RTL-11710B	1150	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	683	70
RTL-12710B	1250	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	683	70
RTL-13710B	1350	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	683	70
RTL-14710B	1450	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	688	70
RTL-11710B-T2	1150	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	683	70

10 Speed

MODEL 10 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
RTL-12710B-T2	1250	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	683	70
RTL-13710B-T2	1350	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	683	70
RTL-14710B-T2	1450	14.84		17.34	12.83					14.84	35	10.98	35	8.13	35	6.02	35	4.46	35	3.30	34	2.47	35	1.83	35	1.35	35	1.00	32.4	688	70
RTO-910	950			7.15	2.21					6.59	28	5.16	26	4.08	26	3.24	24	2.62	29	2.04	28	1.59	26	1.26	26	1.00	24	0.81	28.9	576	87
RTO-1110	1100			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	30.9	620	89
RTO-6610	660	8.94		7.62	2.23					7.17	28	5.61	28	4.38	28	3.42	25	2.74	31	2.10	28	1.64	28	1.28	28	1.00	28	0.80	28.3	359	90
RTO-11610	1150	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.81	28	2.20	31	1.68	29	1.30	30	1.00		0.78	28.9	598	85
RTO-12510	1250			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	32.8	698	89
RTO-12610	1250	9.96		7.73	2.17					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	28.9	609	86
RTO-14610	1450	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	29.5	621	86
RTO-15210C	1550	17.17		13.75	2.80					12.69	37	9.29	38	6.75	37	4.90	36	3.62	40	2.59	37	1.90	38	1.38	37	1.00	36	0.74	29.9	602	84
RTO-16210C	1650	17.17		13.75	2.80					12.69	37	9.29	38	6.75	37	4.90	36	3.62	40	2.59	37	1.90	38	1.38	37	1.00	35	0.74	29.9	588	84
RTO-958LL	950		13.69	9.17	2.86	13.10		8.77		5.85		4.29		3.20		2.37		1.83		1.34		1.00		0.74					34.1	658	94
RTO-1258LL	1250		13.75	9.63	2.86	13.15		9.21		6.15		4.51		3.36		2.49		1.83		1.34		1.00		0.74					36.5	768	94
RTO-11608LL	1150		14.69	9.83	2.89	14.05		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					32.1	644	R-.935 / L-.935
RTO-11708LL	1150	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					32.1	675	94
RTO-11908LL	1150	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.1	690	94
RTO-14608LL	1650	19.58	15.33	9.83	2.89	14.66	55	9.41	51	6.23	35	4.62	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.6	698	R-.935 / L-.935
RTO-14708LL	1650	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.6	690	94
RTO-14908LL	1450	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.1	690	94
RTO-16908LL	1650	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.1	690	94
RTF-11610	1150	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	28.90	598	70
RTF-12510	1250			9.71	2.74					9.71		7.49		5.83		4.50		3.55		2.74		1.65		1.27		1.00			32.8	698	70
RTF-12610	1250	9.96		9.84	2.76					9.96	31	7.63	29	5.90	30	4.54	27	3.57	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	28.9	609	70
RTF-12710B	1250	14.78		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	28.9	606	70
RTF-14610	1450	9.96		9.84	2.76					9.96		7.63		5.90		4.54		3.57		2.79		2.14		1.65		1.27		1.00	29.5	621	70
RTF-14710B	1450	14.73		15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00	29.5	624	70
RTOF-1110	1100			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	30.9	620	89
RTOF-11610	1150	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.81	28	2.20	31	1.68	29	1.30	30	1.00		0.78	28.9	598	85
RTOF-12510	1250			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	32.8	698	89
RTOF-12610	1250	9.96		7.73	2.17					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	28.9	609	86
RTOF-14610	1450	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	29.5	621	86
RTOF-958LL	950		13.69	9.17	2.86	13.10		8.77		5.85		4.29		3.20		2.37		1.83		1.34		1.00		0.74					34.1	658	94
RTOF-1258LL	1250		13.75	9.63	2.86	13.15		9.21		6.15		4.51		3.36		2.49		1.83		1.34		1.00		0.74					36.5	768	94
RTOF-11608LL	1150		14.69	9.83	2.89	14.05		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					32.1	644	R-.935 / L-.935
RTOF-11908LL	1150	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.1	690	94
RTOF-14608LL	1650		15.33	9.83	2.89	14.66		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					33.6	698	94
RTOF-14708LL	1650	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.6	690	94
RTOF-14908LL	1450	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.1	690	94
RTOF-16908LL	1650	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.1	690	94
RTX-1110	1100			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	30.9	620	89
RTX-11610	1150	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.81	28	2.20	31	1.68	29	1.30	30	1.00		0.78	28.9	598	85
RTX-11710B	1150	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	28.9	604	94
RTX-11710C	1150	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	28.9	604	79
RTX-12510	1250			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	32.8	698	89
RTX-12610	1250	9.96		7.73	2.17					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	28.9	609	86
RTX-12710B	1250	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	28.9	606	94

10 Speed

MODEL 10 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
RTX-12710C	1250	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	28.9	606	79
RTX-13710B	1350	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	28.9	611	94
RTX-13710C	1350	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	28.9	611	79
RTX-14610	1450	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	29.5	621	86
RTX-14710B	1450	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	29.5	624	94
RTX-14710C	1450	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	29.5	624	79
RTX-15710B	1550	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	29.5	634	94
RTX-15710C	1550	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	29.5	634	79
RTX-16710B	1650	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	29.5	634	94
RTX-16710C	1650	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	29.5	710	79
RTX-1258LL	1250		13.75	9.63	2.86	13.15		9.21		6.15		4.51		3.36		2.49		1.83		1.34		1.00		0.74					36.5	768	94
RTX-11608LL	1150		14.69	9.83	2.89	14.05		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					32.1	644	R-.935 / L-.935
RTX-11708LL	1150	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					32.1	698	94
RTX-14608LL	1650		15.33	9.83	2.89	14.66		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					33.6	698	94
RTX-14708LL	1650	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.6	690	94
RTXF-1110	1100			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	30.9	620	89
RTXF-11610	1150	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.81	28	2.20	31	1.68	29	1.30	30	1.00		0.78	28.9	598	85
RTXF-11710B	1150	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	28.9	604	94
RTXF-11710C	1150	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	28.9	604	79
RTXF-12510	1250			7.65	2.16					7.65		5.90		4.59		3.55		2.79		2.16		1.66		1.30		1.00		0.79	32.8	698	89
RTXF-12610	1250	9.96		7.73	2.17					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	28.9	609	86
RTXF-12710B	1250	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	28.9	606	94
RTXF-12710C	1250	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	28.9	606	79
RTXF-13710B	1350	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	28.9	611	94
RTXF-13710C	1350	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	28.9	611	79
RTXF-14610	1450	9.96		7.73	2.16					7.83	31	6.00	29	4.63	30	3.57	27	2.80	28	2.19	31	1.68	29	1.30	30	1.00		0.78	29.5	621	86
RTXF-14710B	1450	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	29.5	624	94
RTXF-14710C	1450	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	29.5	624	79
RTXF-15710B	1550	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	29.5	634	94
RTXF-15710C	1550	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	29.5	634	79
RTXF-16710B	1650	14.78		11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74	29.5	634	94
RTXF-16710C	1650	17.52		13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73	29.5	710	79
RTXF-1258LL	1250		13.75	9.63	2.86	13.15		9.21		6.15		4.51		3.36		2.49		1.83		1.34		1.00		0.74					36.5	768	94
RTXF-11608LL	1150		14.69	9.83	2.89	14.05		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					32.1	644	R-.935 / L-.935
RTXF-11708LL	1150	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					32.1	698	94
RTXF-14608LL	1650		15.33	9.83	2.89	14.66		9.41		6.23		4.62		3.40		2.53		1.83		1.36		1.00		0.74					33.6	698	94
RTXF-14708LL	1650	19.58	15.22	9.85	2.89	14.56	55	9.42	51	6.24	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74					33.6	690	94
RTLO-11610B	1150	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLO-12610B	1250	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLO-13610B	1350	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLO-14610A	1450	13.27		12.28	9.27					10.02	32	7.56	34	5.63	32	4.25	35	3.16	32	2.38	34	1.78	32	1.35	35	1.00	32	0.75	32.4	634	70
RTLO-14610B	1450	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-15610B	1550	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-16610B	1650	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-17610B	1750	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-18610B	1850	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70

10 Speed

MODEL 10 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																												
RTLO-11610B-T2	1150	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLO-12610B-T2	1250	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLO-13610B-T2	1350	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLO-14610B-T2	1450	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-15610B-T2	1550	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-16610B-T2	1650	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-17610B-T2	1750	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLO-18610B-T2	1850	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-11610B	1150	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLOF-12610B	1250	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLOF-13610B	1350	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLOF-14610B	1450	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-15610B	1550	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-16610B	1650	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-17610B	1750	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-18610B	1850	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-11610B-T2	1150	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLOF-12610B-T2	1250	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLOF-13610B-T2	1350	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.1	625	70
RTLOF-14610B-T2	1450	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-15610B-T2	1550	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-16610B-T2	1650	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70
RTLOF-17610B-T2	1750	14.93		12.93	9.58					11.06	35	8.20	35	6.06	35	4.49	35	3.32	35	2.46	35	1.82	35	1.35	35	1.00	35	0.74	32.4	630	70

11 Speed

MODEL 11 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	LL	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																									
RTO-11709MLL	1150	35.71	25.21	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.6	671	79
RTO-11909ALL	1150	35.71	20.84	13.03	3.43	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	671	79
RTO-11909MLL	1150	35.71	25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	671	79
RTO-14709MLL	1450	35.71	25.21	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.6	673	79
RTO-14909ALL	1450	35.71	20.84	13.03	3.43	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	671	79
RTO-14909MLL	1450	35.71	25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	673	79
RTO-16909ALL	1650	35.71	20.84	13.03	3.43	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	698	79
RTOF-11709MLL	1150	35.71	25.21	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.6	671	79
RTOF-11909ALL	1150	35.71	20.84	13.03	3.43	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	671	79
RTOF-11909MLL	1150	35.71	25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	671	79
RTOF-14709MLL	1450	35.71	25.21	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.6	673	79
RTOF-14909ALL	1450	35.71	20.84	13.03	3.43	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	671	79
RTOF-14909MLL	1450	35.71	25.22	15.76	4.15	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	673	79
RTOF-16909ALL	1650	35.71	20.84	13.03	3.43	26.08	60	16.30	37	11.85	60	7.41	42	5.23	38	3.79	37	2.77	42	1.95	42	1.38	38	1.00	37	0.73	33.1	698	79

12 & 13 Speed

MODEL 12 SPEED SNAPPER	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																									
TS-1312A	1300		8.16	10.17	6.56					11.19		8.97		7.22		5.84		4.68		3.77		2.99		2.40		35.4	766	

MODEL 13 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																									
RT-613	600	NA	19.00	9.12	2.77	H L		18.00	28	14.04	28	19.96	27	8.64	28	6.74	28	4.09 5.26	28 28	2.62 3.29	29 28	1.60 2.05	29 28	1.00 1.24	24	34.7	622	73
RT-6613	660	17.93	19.06	9.15	2.78	H L		17.93	28	14.04	28	10.96	27	8.61	28	6.74	28	4.11 5.26	25 28	2.61 3.29	28 26	1.60 2.05	28 28	1.00 1.25	25	32.7	554	72
RT-9513	950			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.47 2.86		1.81 2.10		1.35 1.56		1.00 1.16		34.1	660	70
RT-11613	1150	12.56		13.13	3.89	H L	Splitter 16%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	18	2.46 2.86	16 16	1.83 2.12	17 16	1.35 1.56	16 16	1.00 1.16	16	32.1	652	70
RT-12513	1250			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.47 2.86		1.81 2.10		1.35 1.56		1.00 1.16		35.6	725	70
RT-14613	1450	12.56		13.13	3.89	H L	Splitter 16%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	18	2.46 2.86	16 16	1.83 2.12	17 16	1.35 1.56	16 16	1.00 1.16	16	32.4	659	70
RT-15613	1650	12.56		13.13	3.89	H L	Splitter 16%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	18	2.46 2.86	16 16	1.83 2.12	17 16	1.35 1.56	16 16	1.00 1.16	16	32.4	665	70
RTF-9513	950			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.47 2.86		1.81 2.10		1.35 1.56		1.00 1.16		34.1	660	70
RTF-11613	1150	12.56		13.13	3.89	H L	Splitter 16%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	18	2.46 2.86	16 16	1.83 2.12	17 16	1.35 1.56	16 16	1.00 1.16	16	32.1	652	70
RTF-12513	1250			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.47 2.86		1.81 2.10		1.35 1.56		1.00 1.16		35.6	725	70
RTF-14613	1450	12.56		13.13	3.89	H L	Splitter 16%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	18	2.46 2.86	16 16	1.83 2.12	17 16	1.35 1.56	16 16	1.00 1.16	16	32.4	659	70
RTF-15613	1650	12.56		13.13	3.89	H L	Splitter 16%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	18	2.46 2.86	16 16	1.83 2.12	17 16	1.35 1.56	16 16	1.00 1.16	16	32.4	665	70
RTO-613	600		15.30	7.35	2.23	H L		14.50		11.31		8.83		6.96		5.43		3.29 4.24		2.11 2.65		1.29 1.65		.80 1.00		34.7	622	90
RTO-6613	650	17.93	15.28	7.34	2.23	H L		14.38	28	11.26	28	8.79	27	6.91	28	5.41	28	3.29 4.22	25 28	2.10 2.64	28 26	1.28 1.64	28 26	0.80 1.00	26	32.7	554	90
RTO-913	835			13.07	3.87	H L	Splitter 15%	12.50	50	8.35	36	6.12	34	4.56	35	3.38	37	2.14 2.47	18 15	1.57 1.81	16 15	1.17 1.35	17 15	.87 1.00	15	32.1	710	70
RTO-9513	950			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.14 2.47		1.57 1.81		1.17 1.35		0.87 1.00		34.1	660	70
RTO-11613	1150	14.40		13.13	3.89	H L	Splitter 15%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	37	2.15 2.46	18 15	1.60 1.83	19 15	1.17 1.35	17 15	.87 1.00	15	32.1	652	70
RTO-11813	1150	14.40		13.13	3.89	H L		12.56		8.32		6.18		4.54		3.38		2.15 2.46		1.60 1.83		1.17 1.35		.87 1.00		32.1	652	70
RTO-12513	1250			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.14 2.47		1.57 1.81		1.17 1.35		.87 1.00		35.6	725	70
RTO-14613	1450	14.40		13.13	3.89	H L	Splitter 15%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	37	2.15 2.46	18 15	1.60 1.83	19 15	1.17 1.35	17 15	.87 1.00	15	32.4	659	70
RTO-14813	1400	14.40		13.13	3.89	H L		12.56		8.32		6.18		4.54		3.38		2.15 2.46		1.60 1.83		1.17 1.35		.87 1.00		32.4	659	70
RTO-15613	1650	14.40		13.13	3.89	H L	Splitter 15%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	37	2.15 2.46	18 15	1.60 1.83	19 15	1.17 1.35	17 15	.87 1.00	15	32.4	665	70
RTO-15813	1650	12.56		13.13	3.89	H L		12.56		8.32		6.18		4.54		3.38		2.15 2.46		1.60 1.83		1.17 1.35		.87 1.00		32.4	665	70
RTOF-9513	950			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.14 2.47		1.57 1.81		1.17 1.35		0.87 1.00		34.1	660	70
RTOF-11613	1150	14.40		13.13	3.89	H L	Splitter 15%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	37	2.15 2.46	18 15	1.60 1.83	19 15	1.17 1.35	17 15	.87 1.00	15	32.1	652	70
RTOF-11813	1150	14.40		13.13	3.89	H L		12.56		8.32		6.18		4.54		3.38		2.15 2.46		1.60 1.83		1.17 1.35		.87 1.00		32.1	652	70
RTOF-12513	1250			13.07	3.87	H L		12.50		8.35		6.12		4.56		3.38		2.14 2.47		1.57 1.81		1.17 1.35		.87 1.00		35.6	725	70
RTOF-14613	1450	14.40		13.13	3.89	H L	Splitter 15%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	37	2.15 2.46	18 15	1.60 1.83	19 15	1.17 1.35	17 15	.87 1.00"	15	32.4	659	70
RTOF-14813	1400	14.40		13.13	3.89	H L		12.56		8.32		6.18		4.54		3.38		2.15 2.46		1.60 1.83		1.17 1.35		.87 1.00		32.4	659	70

12 & 13 Speed

MODEL 13 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	LL	%	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																									
RTOF-15613	1650	14.40		13.13	3.89	H L	Splitter 15%	12.56	51	8.32	35	6.18	36	4.54	34	3.38	37	2.15 2.46	18 15	1.60 1.83	19 15	1.17 1.35	17 15	.87 1.00	15	32.4	665	70
RTOF-15813	1650	12.56		13.13	3.89	H L		12.56		8.32		6.18		4.54		3.38		2.15 2.46		1.60 1.83		1.17 1.35		.87 1.00		32.4	665	70
RTLO-12713A	1250	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.1	714	79
RTLO-12913A	1250	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17	.73 .86		33.1	714	79
RTLO-14613B	1400	17.40		14.71	3.89	H L	Splitter 18%	14.71	44	10.20	39	7.34	40	5.26	39	3.78	4	2.28 2.70	18 18	1.64 1.94	18 18	1.18 1.39	18 18	.85 1.00	18	32.4	748	70
RTLO-14713A	1450	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.4	714	79
RTLO-14913A	1450	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	714	79
RTLO-16713A	1650	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.4	716	79
RTLO-16913A	1650	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLO-18913A	1850	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLO-20913A	2050	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLO-14913A-T2	1450	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	714	79
RTLO-16913A-T2	1650	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLO-18913A-T2	1850	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLOF-12713A	1250	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.1	714	79
RTLOF-12913A	1250	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17	.73 .86		33.1	714	79
RTLOF-14613B	1400	17.40		14.71	3.89	H L	Splitter 18%	14.71	44	10.20	39	7.34	40	5.26	39	3.78	4	2.28 2.70	18 18	1.64 1.94	18 18	1.18 1.39	18 18	.85 1.00	18	32.4	748	70
RTLOF-14713A	1450	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.4	714	79
RTLOF-14913A	1450	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	714	79
RTLOF-16713A	1650	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.4	716	79
RTLOF-16913A	1650	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLOF-18913A	1850	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLOF-20913A	2050	16.86		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLOF-16713A-T2	1650	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		32.4	716	79
RTLOF-16913A-T2	1650	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTLOF-18913A-T2	1850	16.90		13.22	3.50	H L	Splitter 17%	12.31	42	8.64	42	6.11	38	4.43	37	3.23	41	1.95 2.29	21 21	1.38 1.62	18 18	1.00 1.17	17 17	.73 .86		33.1	716	79
RTOO-9513	950			13.07	3.87	H L		12.10		7.28		5.10		3.69		2.70		1.66 1.97		1.16 1.38		1.84 1.00		.62 .73		34.1	660	79
RTOO-11613	1150	19.52		12.68	3.43	H L	Splitter 18%	12.13	68	7.21	42	5.09	38	3.69	37	2.70	88	1.66 1.95	20 18	1.17 1.38	17 18	.85 1.00	17 18	.62 .73	18	32.1	652	79
RTOO-14613	1450	19.52		12.68	3.43	H L	Splitter 18%	12.13	68	7.21	42	5.09	38	3.69	37	2.70	88	1.66 1.95	20 18	1.17 1.38	17 18	.85 1.00	17 18	.62 .73	18	32.4	659	79
RTOOF-9513	728			12.66	3.43	H L	Splitter 19%	12.10	66	7.28	43	5.10	38	3.69	37	2.70	37	1.66 1.97	19 19	1.16 1.38	16 19	.84 1.00	15 19	.62 .73	19	32.1	660	70
RTOOF-11613	1150	19.52		12.68	3.43	H L	Splitter 18%	12.13	68	7.21	42	5.09	38	3.69	37	2.70	88	1.66 1.95	20 18	1.17 1.38	17 18	.85 1.00	17 18	.62 .73	18	32.1	652	79
RTOOF-14613	1450	19.52		12.68	3.43	H L	Splitter 18%	12.13	68	7.21	42	5.09	38	3.69	37	2.70	88	1.66 1.95	20 18	1.17 1.38	17 18	.85 1.00	17 18	.62 .73	18	32.4	659	79

15 Speed

MODEL 15 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	NOTES	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																									
RT-915	950	NA	13.19	8.83	2.73	Deep Reduction	8.14 12.16	28	6.38 9.53	26	5.05 7.54	26	4.00 5.97	24	3.24 4.84	29	2.51	28	1.97	26	1.56	26	1.24	24	1.00	32.1	770	70
RT-11715	1150	15.40	15.21	9.84	2.76	Deep Reduction	9.96 15.40	31	7.63 11.80	29	5.90 9.11	30	4.54 7.02	27	3.57 5.52	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	32.1	681	70
RT-12515	1250		13.87	9.71	2.74	Deep Reduction	9.71 13.87		7.49 10.70		5.83 8.34		4.50 6.43		3.55 5.07		2.74		2.11		1.65		1.27		1.00	36.5	770	89
RT-11615	1150		14.69	9.84	2.76	Deep Reduction	9.96 14.88	30	7.63 11.40	29	5.90 8.81	30	4.54 6.78	27	3.57 5.33	28	2.79	30	2.14	30	1.65	30	1.27	27	1.00	32.1	648	70
RT-14615	1450		15.33	9.84	2.76	Deep Reduction	9.96 15.52	30	7.63 11.89	29	5.90 9.19	30	4.54 7.08		3.57 5.56		2.79		2.14		1.65		1.27		1.00	33.6	703	70
RT-14715	1450	15.40	15.21	9.84	2.76	Deep Reduction	9.96 15.40	31	7.63 11.80	29	5.90 9.11	30	4.54 7.02	27	3.57 5.52	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.6	696	70
RT-14915	1450	16.94	16.72	9.84	2.76	Deep Reduction	9.96 16.94	31	7.68 16.94	29	5.90 10.03	30	4.54 7.73	27	3.57 6.07	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.1	696	70
RT-15615	1550		15.33	9.84	2.76	Deep Reduction	9.96 15.52	30	7.63 11.89	29	5.90 9.19	30	4.54 7.08	27	3.57 5.56	28	2.79	30	2.14	30	1.65	30	1.27	27	1.00	33.6	703	70
RT-15715	1550	15.40	15.21	9.84	2.76	Deep Reduction	9.96 15.40	31	7.63 11.80	29	5.90 9.11	30	4.54 7.02	27	3.57 5.52	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.6	696	70
RTF-915	950	NA	13.19	8.83	2.73	Deep Reduction	8.14 12.17	29	6.38 9.54	27	5.05 7.55	27	4.00 5.98	25	3.24 4.85	30	2.51	29	1.97	27	1.56	27	1.24	25	1.00	33.1	770	70
RTF-11615	1150		14.69	9.84	2.76	Deep Reduction	9.96 14.88		7.63 11.40		5.90 8.81		4.54 6.78		3.57 5.33		2.79		2.14		1.65		1.27		1.00	32.1	648	70
RTF-14615	1450		15.33	9.84	2.76	Deep Reduction	9.96 15.52		7.63 11.89		5.90 9.19		4.54 7.08		3.57 5.56		2.79		2.14		1.65		1.27		1.00	33.6	703	70
RTF-14715	1450	15.40	15.21	9.84	2.76	Deep Reduction	9.96 15.40	31	7.63 11.80	29	5.90 9.11	30	4.54 7.02	27	3.57 5.52	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.6	696	70
RTF-14915	1450	16.94	16.72	9.84	2.76	Deep Reduction	9.96 16.94	31	7.68 16.94	29	5.90 10.03	30	4.54 7.73	27	3.57 6.07	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.1	696	70
RTF-15615	1550		15.33	9.84	2.76	Deep Reduction	9.96 15.52		7.63 11.89		5.90 9.19		4.54 7.08		3.57 5.56		2.79		2.14		1.65		1.27		1.00	33.6	703	70
RTO-915	950	NA	10.67	7.15	2.21	Deep Reduction	6.59 9.84	28	5.16 7.71	26	4.08 6.10	26	3.24 4.84	24	2.62 3.91	29	2.04	28	1.59	26	1.26	26	1.00	24	0.81	32.1	770	87
RTO-11615	1150		11.54	7.73	2.16	Deep Reduction	7.83 11.69	30	6.00 8.96	30	4.63 6.92	30	3.57 5.33	27	2.80 4.19	28	219	30	1.68	24	1.30	30	1.00	28	0.78	32.1	648	89
RTO-11715	1150	15.40	11.95	7.73	2.17	Deep Reduction	7.83 11.69	31	6.00 8.96	29	4.63 6.92	30	3.57 5.52	27	2.81 4.34	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	32.1	681	89
RTO-12515	1250		10.93	7.65	2.16	Deep Reduction	7.65 10.93		5.90 8.43		4.59 6.56		3.55 5.07		2.79 3.99		2.16		1.66		1.30		1.00		0.79	36.5	770	
RTO-14615	1450		12.04	7.73	2.16	Deep Reduction	7.83 12.20	30	6.00 9.35	30	4.63 7.22	30	3.57 5.56	28	2.80 4.37	28	2.19	30	1.68	29	1.30	30	1.00	28	0.78	33.6	703	89
RTO-14715	1450	15.40	11.95	7.73	2.17	Deep Reduction	7.83 12.10	31	6.00 9.27	29	4.63 7.16	30	3.57 5.52	27	2.81 4.43	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.6	696	89
RTO-14915	1450	16.94	13.14	7.73	2.17	Deep Reduction	7.83 13.31	31	6.00 10.20	29	4.63 7.88	30	3.57 6.07	27	2.81 4.77	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.1	696	89
RTO-15615	1550		12.04	7.73	2.16	Deep Reduction	7.83 12.20	30	6.00 9.35	30	4.63 7.22	30	3.57 5.56	28	2.80 4.37	28	2.19	30	1.68	29	1.30	30	1.00	28	0.78	33.6	703	89
RTO-15715	1550	15.40	11.95	7.73	2.17	Deep Reduction	7.83 12.10	31	6.00 9.27	29	4.63 7.16	30	3.57 5.52	27	2.81 4.43	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.6	696	89
RTO-16915	1650	16.94	13.14	7.73	2.17	Deep Reduction	7.83 13.31	31	6.00 10.20	29	4.63 7.88	30	3.57 6.07	27	2.81 4.77	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.1	696	89

15 Speed

MODEL 15 SPEED	Lbs-Ft. Max TQ.	Over All	LL	L	H	NOTES	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																									
RTOF-915	950	NA	10.67	7.15	2.21	Deep Reduction	6.59 9.84	28	5.16 7.71	26	4.08 6.10	26	3.24 4.84	24	2.62 3.91	29	2.04	28	1.59	26	1.26	26	1.00	24	0.81	32.1	770	87
RTOF-11615	1150		11.54	7.73	2.16	Deep Reduction	7.83 11.69		6.00 8.96		4.63 6.92		3.57 5.33		2.80 4.19		219		1.68		1.30		1.00		0.78	32.1	648	89
RTOF-12515	1250		10.93	7.65	2.16	Deep Reduction	7.65 10.93		5.90 8.43		4.59 6.56		3.55 5.07		2.79 3.99		2.16		1.66		1.30		1.00		0.79	36.5	770	
RTOF-14615	1450		12.04	7.73	2.16	Deep Reduction	7.83 12.20		6.00 9.35		4.63 7.22		3.57 5.56		2.80 4.37		2.19		1.68		1.30		1.00		0.78	33.6	703	89
RTOF-14915	1450	16.94	13.14	7.73	2.17	Deep Reduction	7.83 13.31	31	6.00 10.20	29	4.63 7.88	30	3.57 6.07	27	2.81 4.77	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.1	696	89
RTOF-15615	1550		12.04	7.73	2.16	Deep Reduction	7.83 12.20		6.00 9.35		4.63 7.22		3.57 5.56		2.80 4.37		2.19		1.68		1.30		1.00		0.78	33.6	703	89
RTOF-16915	1650	16.94	13.14	7.73	2.17	Deep Reduction	7.83 13.31	31	6.00 10.20	29	4.63 7.88	30	3.57 6.07	27	2.81 4.77	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.1	696	89
RTX-11615	1150		11.54	7.73	2.16	Deep Reduction	7.83 11.69		6.00 8.96		4.63 6.92		3.57 5.33		2.80 4.19		219		1.68		1.30		1.00		0.78	32.1	648	89
RTX-14615	1450		12.04	7.73	2.16	Deep Reduction	7.83 12.20		6.00 9.35		4.63 7.22		3.57 5.56		2.80 4.37		2.19		1.68		1.30		1.00		0.78	33.6	703	89
RTO-14715	1450	15.40	11.95	7.73	2.17	Deep Reduction	7.83 12.10	31	6.00 9.27	29	4.63 7.16	30	3.57 5.52	27	2.81 4.43	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.6	696	89
RTX-15615	1550		12.04	7.73	2.16	Deep Reduction	7.83 12.20		6.00 9.35		4.63 7.22		3.57 5.56		2.80 4.37		2.19		1.68		1.30		1.00		0.78	33.6	703	89
RTX-15715	1550	15.40	15.21	9.84	2.76	Deep Reduction	9.96 15.40	31	7.63 11.80	29	5.90 9.11	30	4.54 7.02	27	3.57 5.52	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.6	696	70
RTXF-14615	1450		12.04	7.73	2.16	Deep Reduction	7.83 12.20		6.00 9.35		4.63 7.22		3.57 5.56		2.80 4.37		2.19		1.68		1.30		1.00		0.78	33.6	703	89
RTO-14715	1450	15.40	11.95	7.73	2.17	Deep Reduction	7.83 12.10	31	6.00 9.27	29	4.63 7.16	30	3.57 5.52	27	2.81 4.43	28	2.19	31	1.68	29	1.30	30	1.00	27	0.79	33.6	696	89
RTXF-15615	1550		12.04	7.73	2.16	Deep Reduction	7.83 12.20		6.00 9.35		4.63 7.22		3.57 5.56		2.80 4.37		2.19		1.68		1.30		1.00		0.78	33.6	703	89
RTXF-15715	1550	15.40	15.21	9.84	2.76	Deep Reduction	9.96 15.40	31	7.63 11.80	29	5.90 9.11	30	4.54 7.02	27	3.57 5.52	28	2.79	31	2.14	29	1.65	30	1.27	27	1.00	33.6	696	70

18 Speed

MODEL 18 SPEED	Lbs-Ft. Max TQ.	Over All	LL	H		%		L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																								
RTO-15618	1550	17.39	12.45 14.71	3.29 3.89	H L	Splitter 18%	O\D DIR	12.45 14.71	44	8.62 10.20	39	6.21 7.34	40	4.45 5.26	39	3.20 3.78	40	2.28 2.70	39	1.64 1.94	40	1.18 1.39	39	0.85 1.00	32.4	672	70
RTOF-15618	1550	17.39	12.45 14.71	3.29 3.89	H L	Splitter 18%	O\D DIR	12.45 14.71	44	8.62 10.20	39	6.21 7.34	40	4.45 5.26	39	3.20 3.78	40	2.28 2.70	39	1.64 1.94	40	1.18 1.39	39	0.85 1.00	32.4	748	70
RTLO-14618A	1450	17.39	12.45 14.71	3.29 3.89	H L	Splitter 18%	O\D DIR	12.45 14.71	44	8.62 10.20	39	6.21 7.34	40	4.45 5.26	39	3.20 3.78	40	2.28 2.70	39	1.64 1.94	40	1.18 1.39	39	0.85 1.00	32.4	662	70
RTLO-14718B	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLO-14918A	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-14918B	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-16618A	1650	17.39	12.45 14.71	3.29 3.89	H L	Splitter 18%	O\D DIR	12.45 14.71	44	8.62 10.20	39	6.21 7.34	40	4.45 5.26	39	3.20 3.78	40	2.28 2.70	39	1.64 1.94	40	1.18 1.39	39	0.85 1.00	32.4	672	70
RTLO-16718B	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLO-16918B	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-18718B	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLO-18918B	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-20918B	2050	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-22918B	2250	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-14718B-T2	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLO-16718B-T2	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLO-16918B-T2	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-18718B-T2	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLO-18918A-T2	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLO-20918B-T2	2050	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLOF-14618A	1450	17.39	12.45 14.71	3.29 3.89	H L	Splitter 18%	O\D DIR	12.45 14.71	44	8.62 10.20	39	6.21 7.34	40	4.45 5.26	39	3.20 3.78	40	2.28 2.70	39	1.64 1.94	40	1.18 1.39	39	0.85 1.00	32.4	662	70
RTLOF-14718B	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLOF-14918B	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLOF-16618A	1650	17.39	12.45 14.71	3.29 3.89	H L	Splitter 18%	O\D DIR	12.45 14.71	44	8.62 10.20	39	6.21 7.34	40	4.45 5.26	39	3.20 3.78	40	2.28 2.70	39	1.64 1.94	40	1.18 1.39	39	0.85 1.00	32.4	672	70
RTLOF-16718B	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLOF-16918B	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLOF-18718B	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	32.4	716	79
RTLOF-18918B	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLOF-20918B	2050	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79
RTLOF-22918B	2250	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	O\D DIR	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86	33.1	716	79

Fuller Advantage Manual

MODEL FULLER ADVANTAGE MANUAL	Lbs-Ft. Max TQ.	Over All	R1	R2	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																							
FA-11810B	1150	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	29.9	541	70
FA-12810B	1250	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	29.9	541	70
FA-13810B	1350	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	29.9	541	70
FA-14810B	1450	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	29.9	541	70
FA-15810B	1550	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	29.9	541	70
FAM-15810B	1550*	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	29.9	541	70
FAO-11810C	1150	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAO-12810C	1250	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAO-13810C	1350	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAO-14810C	1450	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAO-15810C	1550	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAO-16810C	1650	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAOM-14810C	1450*	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAOM-15810C	1550*	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79
FAOM-16810C	1650*	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	29.9	541	79

* +200 lbs.-ft. [271 Nm] in top two gears

Ceemat

MODEL CEEMAT	Lbs-Ft. Max TQ.	Over All	L	H	L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																					
RTO-11109A-AT	1150	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1036	94
RTO-13109A-AT	1350	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1036	94
RTO-14109A-AT	1450	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1036	94
RTO-11109B-AT	1150	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1036	79
RTO-13109B-AT	1350	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1036	79
RTO-14109B-AT	1450	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1036	79
RTO-11109A-ATE	1150	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1029	94
RTO-11109B-ATE	1150	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-13109A-ATE	1350	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1029	94
RTO-13109B-ATE	1350	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-14109A-ATE	1450	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1029	94
RTO-14109B-ATE	1450	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-16109A-ATE	1650	12.65	9.83	2.89	9.41	51	6.23	35	4.63	36	3.40	34	2.53	38	1.83	35	1.36	36	1.00	34	0.74	34.97	1029	94
RTO-16109B-ATE	1650	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-11109B-ATE	1150	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-13109B-ATE	1350	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-14109B-ATE	1450	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79
RTO-16109B-ATE	1650	17.21	13.14	3.43	12.56	68	7.47	42	5.28	38	3.82	37	2.79	43	1.95	42	1.38	38	1.00	37	0.73	34.97	1029	79

C - Converter
E - Enhanced
E - Electronically
M - Managed
A - Automatic
T - Transmission

Autoshift-Autoselect-Ultrashift

MODEL AUTOSHIFT 6 SPEED	Lbs-Ft. Max TQ.	Over All					L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
FO-6406A-ASX	660	9.04	6.75						7.05	71	4.13	64	2.52	58	1.59	59	1.00	28	0.78														25.6	422	67
FO-8406A-ASX	860	9.04	6.75						7.05	71	4.13	64	2.52	58	1.59	59	1.00	28	0.78														25.6	422	67

MODEL ULTRASHIFT 6 SPEED	Lbs-Ft. Max TQ.	Over All					L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
FO-6406A-ASW	660	9.04	6.75						7.05	71	4.13	64	2.52	58	1.59	59	1.00	28	0.78														30.2	602	67
FO-8406A-ASW	860	9.04	6.75						7.05	71	4.13	64	2.52	58	1.59	59	1.00	28	0.78														30.2	602	67

MODEL AUTOSHIFT 7 SPEED	Lbs-Ft. Max TQ.	Over All					L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
TO-11607B-ASX	1150	12.35	8.99						9.24	73	5.35	66	3.22	58	2.04	49	1.37	37	1.00	34	0.75												28.9	611	68
TO-14607B-ASX	1400	12.35	8.99						9.24	73	5.35	66	3.22	58	2.04	49	1.37	37	1.00	34	0.75												28.9	611	68

MODEL AUTOSHIFT 10 SPEED	Lbs-Ft. Max TQ.	Over All	L	H			L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
RTO-10910B-AS2	1050	14.85	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	646	94
RTO-10910B-AS3	1050	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	646	94
RTO-12910B-AS2	1250	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	646	94
RTO-12910B-AS3	1250	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	646	94
RTO-14910B-AS2	1450	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	656	94
RTO-14910B-AS3	1450	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	656	94
RTO-16910B-AS2	1650	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	656	94
RTO-16910B-AS3	1650	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	656	94
RTO-18910B-AS2	1850	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	656	94
RTO-18910B-AS3	1850	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.9	656	94
RTO-14910C-AS2	1450	17.53	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.9	656	79
RTO-14910C-AS3	1450	17.53	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.9	656	79
RTO-16910C-AS2	1650	17.53	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.9	656	79
RTO-16910C-AS3	1650	17.53	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.9	656	79
RTAO-10710B-AC	1050	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						28.9	626	94
RTAO-10710C-AC	1050	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						28.9	626	79
RTAO-12710B-AC	1250	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						28.9	628	94
RTAO-12710C-AC	1250	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						28.9	628	79
RTAO-14710B-AC	1450	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.5	646	94
RTAO-14710C-AC	1450	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.5	646	79
RTAO-16710B-AC	1650	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.5	656	94
RTAO-16710C-AC	1650	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.5	656	79
RTAO-10710B-AS	1050	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						28.9	626	94
RTAO-10710C-AS	1050	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						28.9	626	79
RTAO-12710B-AS	1250	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						28.9	628	94
RTAO-12710C-AS	1250	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						28.9	628	79
RTAO-14710B-AS	1450	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.5	646	94
RTAO-14710C-AS	1450	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.5	646	79
RTAO-16710B-AS	1650	14.78	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74						29.5	656	94
RTAO-16710C-AS	1650	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73						29.5	656	79

Autoshift-Autoselect-Ultrashift

MODEL ULTRASHIFT 10 SPEED	Lbs-Ft. Max TQ.	Over All	L	H			L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
RTO-10910B-DM2	1050	14.85	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	671	94
RTO-12910B-DM2	1250	14.85	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	671	94
RTO-14910B-DM2	1450	14.85	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	681	94
RTO-16910B-DM2	1650	14.85	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	681	94

MODEL ULTRASHIFT LST 10 SPEED	Lbs-Ft. Max TQ.	Over All	L	H			L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
RTO-10910B-DM3	1050	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	671	94
RTO-12910B-DM3	1250	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	671	94
RTO-14910B-DM3	1450	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	681	94
RTO-16910B-DM3	1650	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	681	94
RTOM-16910B-DM3	1650	14.81	11.23	2.52					10.96	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.9	681	94
FM-14D310B-LST	1450*	14.74	15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00							29.9	681	70
FM-15D310B-LST	1550**	14.74	15.10	3.38					14.78	34	11.00	35	8.17	36	6.00	34	4.46	35	3.31	34	2.46	35	1.83	36	1.34	34	1.00							29.9	681	70

* 1650 LB-FT. IN TOP TOW GEARS - ** 1750 LB-FT. IN TOP TWO GEARS

MODEL ULTRASHIFT LHP 13 SPEED	Lbs-Ft. Max TQ.	Over All	1	2	3		L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
RTLO-16913L-DM3	1650	16.70	13.09	11.17	3.50		12.19		10.40	17	8.51	22	6.05	38	4.38	37	3.20	41	2.28	17	1.94	20	1.62	17	1.38	18	1.17	17	1.00	17	0.86	17	0.73	33.1	751	79
RTLOM-16913L-DM3	1650**	16.70	13.09	11.17	3.50		12.19		10.40	17	8.51	22	6.05	38	4.38	37	3.20	41	2.28	17	1.94	20	1.62	17	1.38	18	1.17	17	1.00	17	0.86	17	0.73	33.1	751	79

** 1750 LB-FT. IN TOP TOW GEARS ONLY, AVAILABLE IN TOP FOUR WITH A CATEPILLAR C13 & C15.

MODEL AUTOSELECT 10 SPEED	Lbs-Ft. Max TQ.	Over All	L	H			L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
RTAO-10710B-AC	1050	14.78	11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							28.9	626	94
RTAO-12710B-AC	1250	14.78	11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							28.9	628	94
RTAO-14710B-AC	1450	14.78	11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.5	646	94
RTAO-16710B-AC	1650	14.78	11.23	2.52					10.99	34	8.18	35	6.07	36	4.46	34	3.32	35	2.46	34	1.83	35	1.36	36	1.00	34	0.74							29.5	656	94
RTAO-10710C-AC	1050	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73							28.9	626	79
RTAO-12710C-AC	1250	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73							28.9	628	79
RTAO-14710C-AC	1450	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73							29.5	646	79
RTAO-16710C-AC	1650	17.52	13.63	2.78					12.80	38	9.25	37	6.76	38	4.90	37	3.58	37	2.61	38	1.89	37	1.38	38	1.00	37	0.73							29.5	656	79

MODEL ULTRASHIFT LED 13 SPEED	Lbs-Ft. Max TQ.	Over All	1	2	3		L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
FO-16D313E-LED	1650	14.25	13.09	11.17	3.50				10.40	43	7.26	41	5.16	38	3.74	37	2.73	20	2.28	17	1.94	20	1.62	17	1.38	18	1.17	17	1.00	17	0.86	17	0.73	33.1	751	79
FOM-16D313E-LED	1650**	14.25	13.09	11.17	3.50				10.40	43	7.26	41	5.16	38	3.74	37	2.73	20	2.28	17	1.94	20	1.62	17	1.38	18	1.17	17	1.00	17	0.86	17	0.73	33.1	751	79

** 1750 LB-FT. IN TOP TOW GEARS ONLY, AVAILABLE IN TOP FOUR WITH A CATEPILLAR C13 & C15.

Autoshift-Autoselect-Ultrashift

MODEL AUTOSHIFT 18 SPEED	Lbs-Ft. Max TQ.	Over All	LL	H			L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
RTLO-14918A-AS	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-14918B-AS	1450	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-14918A-AS2	1450	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.39 12.19	22	7.26 8.51	20	5.16 6.06	18	3.74 4.38	17	2.73 3.20	20	1.38 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-14918A-AS3	1450	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.40 12.19	22	7.26 8.51	20	5.16 6.05	18	3.74 4.38	17	2.73 3.20	20	1.94 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-16918A-AS	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-16918B-AS	1650	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-16918A-AS2	1650	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.39 12.19	22	7.26 8.51	20	5.16 6.06	18	3.74 4.38	17	2.73 3.20	20	1.38 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-16918A-AS3	1650	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.40 12.19	22	7.26 8.51	20	5.16 6.05	18	3.74 4.38	17	2.73 3.20	20	1.94 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-18918A-AS	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-18918B-AS	1850	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-18918A-AS2	1850	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.39 12.19	22	7.26 8.51	20	5.16 6.06	18	3.74 4.38	17	2.73 3.20	20	1.38 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-18918A-AS3	1850	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.40 12.19	22	7.26 8.51	20	5.16 6.05	18	3.74 4.38	17	2.73 3.20	20	1.94 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-20918A-AS	2050	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-20918B-AS	2050	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-20918A-AS2	2050	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.39 12.19	22	7.26 8.51	20	5.16 6.06	18	3.74 4.38	17	2.73 3.20	20	1.38 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-20918A-AS3	2050	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.40 12.19	22	7.26 8.51	20	5.16 6.05	18	3.74 4.38	17	2.73 3.20	20	1.94 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-22918A-AS	2250	19.72	12.85 15.06	3.43 4.03	H L	Splitter 17%	12.29 14.40	44	7.30 8.56	21	5.16 6.05	18	3.74 4.38	17	2.73 3.20	19	1.95 2.29	21	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-22918A-AS2	2250	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.39 12.19	22	7.26 8.51	20	5.16 6.06	18	3.74 4.38	17	2.73 3.20	20	1.38 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79
RTLO-22918A-AS3	2250	16.70	11.17 13.09	2.99 3.50	H L	Splitter 17%	10.40 12.19	22	7.26 8.51	20	5.16 6.05	18	3.74 4.38	17	2.73 3.20	20	1.94 2.28	20	1.38 1.62	18	1.00 1.17	17	0.73 0.86										33.1	738	79

Ultrashift Plus

MODEL ULTRASHIFT PLUS PERFORMANCE	Lbs-Ft. Max TQ.	R4	R3	R2	R1	OVERALL RATIO	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	Length Inches	Weight Lbs.
		Reverse					Forward gears						Forward gears													
FO-14E310C-LAS	1450			2.78	13.62	17.53	12.80	9.25	6.76	4.90	3.58	2.61	1.89	1.38	1.00	0.73									37.42	915
FO-16E310C-LAS	1650			2.78	13.62	17.53	12.80	9.25	6.76	4.90	3.58	2.61	1.89	1.38	1.00	0.73									37.42	915
FOM-14E310C-LAS	1450			2.78	13.62	17.53	12.80	9.25	6.76	4.90	3.58	2.61	1.89	1.38	1.00	0.73									37.42	915
FOM-15E310C-LAS	1550			2.78	13.62	17.53	12.80	9.25	6.76	4.90	3.58	2.61	1.89	1.38	1.00	0.73									37.42	915
FOM-16E310C-LAS	1650			2.78	13.62	17.53	12.80	9.25	6.76	4.90	3.58	2.61	1.89	1.38	1.00	0.73									37.42	915
FM-14E310B-LAS	1450			3.89	18.18	15.43	15.43	11.52	8.55	6.28	4.67	3.30	2.46	1.83	1.34	1.00									37.42	915
FM-15E310B-LAS	1550			3.89	18.18	15.43	15.43	11.52	8.55	6.28	4.67	3.30	2.46	1.83	1.34	1.00									37.42	915
FO-14E313A-MHP	1450		4.03	12.85	15.06	16.84	12.29	8.56	6.05	4.38	3.20	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73						40.61	995
FO-16E313A-MHP	1650		4.03	12.85	15.06	16.84	12.29	8.56	6.05	4.38	3.20	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73						40.61	995
FO-18E313A-MHP	1850		4.03	12.85	15.06	16.84	12.29	8.56	6.05	4.38	3.20	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73						40.61	995
FO-14E318B-MXP	1450	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-16E318B-MXP	1650	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-18E318B-MXP	1850	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-20E313A-MHP	2050		4.03	12.85	15.06	16.84	12.29	8.56	6.05	4.38	3.20	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73						40.61	995
FO-20E318B-MXP	2050	3.43		12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-22E318B-MXP	2250	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995

MODEL ULTRASHIFT PLUS VOCATIONAL	Lbs-Ft. Max TQ.	R4	R3	R2	R1	OVERALL RATIO	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	Length Inches	Weight Lbs.
		Reverse					Forward gears						Forward gears													
FO-14E308LL-VCS	1450		2.89	9.95	15.22	19.68	14.56	9.42	6.24	4.63	3.40	2.53	1.83	1.36	1.00	0.74									40.61	975
FO-16E308LL-VCS	1650		2.89	9.95	15.22	19.68	14.56	9.42	6.24	4.63	3.40	2.53	1.83	1.36	1.00	0.74									40.61	975
FO-14E309ALL-VMS	1450		3.43	13.03	20.84	35.73	26.08	16.30	11.85	7.41	5.23	3.79	2.77	1.95	1.38	1.00	0.73								40.61	955
FO-14E309ALL-VMS	1650		3.43	13.03	20.84	35.73	26.08	16.30	11.85	7.41	5.23	3.79	2.77	1.95	1.38	1.00	0.73								40.61	955
FO-14E318B-VXP	1450	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-16E318B-VXP	1650	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-18E318B-VXP	1850	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-20E318B-VXP	2050	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	995
FO-22E318B-VXP	2250	3.43	4.03	12.85	15.06	19.73	14.40	12.29	8.56	7.30	6.05	5.16	4.38	3.74	3.20	2.73	2.29	1.95	1.62	1.38	1.17	1.00	0.86	0.73	40.61	1045

Fuller Advantage Automated

MODEL FULLER ADVANTAGE EA3	Lbs-Ft. Max TQ.	OverAll	R1	R2	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																							
FAM-14810B-EA3	1450*	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	31.8	850	79
FAM-15810B-EA3	1550*	15.42	18.18	3.89	15.42	34	11.52	35	8.55	36	6.28	34	4.67	42	3.3	34	2.46	34	1.83	37	1.34	34	1	31.8	850	79
FAO-14810C-EA3	1450	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	31.8	850	79
FAO-16810C-EA3	1650	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	31.8	850	79
FAOM-14810C-EA3	1450*	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	31.8	850	79
FAOM-15810C-EA3	1550*	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	31.8	850	79
FAOM-16810C-EA3	1650*	17.53	13.63	2.78	12.8	38	9.25	37	6.76	38	4.9	37	3.58	37	2.61	38	1.89	37	1.38	38	1	37	0.73	31.8	850	79

MODEL FULLER ADVANTAGE S-RATIO	Lbs-Ft. Max TQ.	OverAll	Rev Lo	Rev Hi	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																							
FAO-16810S-EP3	1650	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-15810S-EP3	1550	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-13810S-EC3	1350***	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-14810S-EC3	1450*	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-15810S-EC3	1550*	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-18910S-EC3	1850**	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-15810S-EN3	1550*	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79
FAOM-18910S-EN3	1850**	17.7	17.12	3.43	14.11	39	10.12	43	7.06	42	4.98	25	3.97	40	2.83	39	2.03	43	1.42	42	1	26	0.796	31.8	850	79

* +200 lbs.-ft. [271 Nm] in top two gears
** +200 lbs.-ft. [271 Nm] in top three gears
*** +300 lbs.-ft. [407 Nm] in top two gears

Procision

MODEL PROCISION	Lbs-Ft. Max TQ.	OverAll	L	H			L	%	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	%	13	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																																	
EDCO-6F107A	660	10.13	6.15	3.95					6.50	56	4.17	65	2.53	63	1.55	55	1.00	30	0.77	20	0.64												30.1	364	L=39 R=82
EDCO-6F107A-B	660	10.13	6.15	3.95					6.50	56	4.17	65	2.53	63	1.55	55	1.00	30	0.77	20	0.64												30.1	364	L=39 R=82
EDCO-6F107A-P	660	10.13	6.15	3.95					6.50	56	4.17	65	2.53	63	1.55	55	1.00	30	0.77	20	0.64												30.1	364	L=39 R=82

Endurant HD

MODEL 11 SPEED	Lbs-Ft. Max TQ.	OverAll	1	2	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11			Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																											
EE-17F111B	1750	14.43	16.92	12.95	14.41	31	11.05	31	8.44	31	6.46	31	4.95	31	3.79	30	2.91	31	2.23	31	1.71	31	1.31	30	1.00			37.9	657	137

MODEL 12 SPEED	Lbs-Ft. Max TQ.	OverAll	1	2	1	%	2	%	3	%	4	%	5	%	6	%	7	%	8	%	9	%	10	%	11	%	12	Length Inches	Weight Lbs.	PTO Speed (% Of Engine)
			Reverse																											
EEO-14F112C	1450	18.85	16.92	12.95	14.41	31	11.05	31	8.44	31	6.46	31	4.95	31	3.79	30	2.91	31	2.23	31	1.71	31	1.31	30	1.00	31	0.77	37.9	657	137
EEO-15F112C	1550	18.85	16.92	12.95	14.41	31	11.05	31	8.44	31	6.46	31	4.95	31	3.79	30	2.91	31	2.23	31	1.71	31	1.31	30	1.00	31	0.77	37.9	657	137
EEO-16F112C	1650	18.85	16.92	12.95	14.41	31	11.05	31	8.44	31	6.46	31	4.95	31	3.79	30	2.91	31	2.23	31	1.71	31	1.31	30	1.00	31	0.77	37.9	657	137
EEO-17F112C	1750	18.85	16.92	12.95	14.41	31	11.05	31	8.44	31	6.46	31	4.95	31	3.79	30	2.91	31	2.23	31	1.71	31	1.31	30	1.00	31	0.77	37.9	657	137
EEO-18F112C	1850	18.85	16.92	12.95	14.41	31	11.05	31	8.44	31	6.46	31	4.95	31	3.79	30	2.91	31	2.23	31	1.71	31	1.31	30	1.00	31	0.77	37.9	657	137

We have tried to make this catalog comprehensive and factual. We reserve the right, however, to make changes at any time, without notice, in specifications and models. Specifications, dimensions, measurements, ratings and other numbers in this catalog are approximations based on design and engineering drawings,prototypes and laboratory tests.

Eaton
Vehicle Group
P.O. Box 4013
Kalamazoo, MI 49003 USA
800-826-HELP (4357)
www.eaton.com/vehicle

© 2021 Eaton
All Rights Reserved
February 2021

Powering Business Worldwide

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.